

ZURIEL COLLECTION


**МАТТ
BOOK. 23**

80x160cm

ASPHALT CREMA

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm





3 RANDOM
FACE



ASPHALT BEIGE

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm





3 RANDOM
FACE



ASPHALT LIGHT GREY

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm





3 RANDOM
FACE



ASPHALT DARK GREY

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm




3 RANDOM
FACE



NORWAY BIANCO

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm




5 RANDOM
FACE



NORWAY LIGHT GREY

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm





5 RANDOM
FACE



NORWAY GREY

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm



5 RANDOM
FACE



NORWAY NERO

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm



5 RANDOM
FACE



NORWAY IVORY

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm




5 RANDOM
FACE



NORWAY BROWN

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm





5 RANDOM
FACE



NORWAY CHOCO

MATT FINISH
ZURIEL COLLECTION

80 x 160 cm



5 RANDOM
FACE



Technical Specification

CHARACTERISTICS	STANDARD AS PER ISO-13006/En14411 GROUP	VALUES	TEST METHOD
-----------------	---	--------	-------------

REGULATORY PROPERTIES

Deviation in Lenth & Width	0.50%	0.20%	ISO - 10545-2
Deviation in Thickness	0.50%	0.50%	ISO - 10545-2
Straightness of Sides	0.50%	0.20%	ISO - 10545-2
Rectangularity	0.50%	0.20%	ISO - 10545-2
Surface Flatness	0.50%	0.20%	ISO - 10545-2
Color Difference	Unaltered	No Change	ISO - 10545-16
Glossiness	As per Mfg.	>90%	Glossmeter

STRUCTURAL PROPERTIES

Water Absorption	<0.05%	<0.05%	ISO - 10545-3
Apparent Density	>2.00 g/cc	>2.10 g/cc	DIN 51082

MASSIVE MECHANICAL PROPERTIES

Modulus of Repture	Min 35N/MM2	Min 40N/MM2	ISO - 10545-4
Breaking Strength	Min. 1300 N	Min. 2000 N	ISO - 10545-4
Impact Resistance	As per Mfg.	Min. 0.55	ISO - 10545-5

SURFACE MECHANICAL PROPERTIES

Surface Abrasion Resistance	As per Mfg.	Min. class 3	ISO - 10545-7
Moh's Hardness	As per Mfg.	Min. class 4	EN 101

THERMO HYGROMETRIC PROPERTIES

Frost Resistance	No Damage	No Damage	ISO - 10545-12
Thermal Shock Resistance	No Damage	No Damage	ISO - 10545-09
Moisture Expansion	Nil	Nil	ISO - 10545-10
Thermal Expansion	Max 9.0x10 ⁻⁶	Max 6.5x10 ⁻⁶	ISO - 10545-08
Crazing Resistance	As per Mfg.	Min 10 Cycle	ISO - 10545-11

52

CHEMICAL PROPERTIES

Chemical Resistance	No Damage	No Damage	ISO - 10545-13
Stain Resistance	Resistant	Resistant	ISO - 10545-14

SAFETY PROPERTIES

Slip Resistance	As per Mfg.	>0.40	ISO - 10545-17
Fire Resistance	As per Mfg.	Fire Proof	N.A.

Packing Detail

SIZE (in mm)	THICKNESS (APPROX)	PIECES / PER BOX	COVERAGE AREA IN SQ. FT.	BOX WEIGHT (APPROX)
800x1600mm	9mm	2	27.55	51 KG

